



FORE TEST CİHAZLARI
İMALAT SAN. ve ULUSLARARASI TİC. A.Ş.
"Yüksek Test Teknolojileri" www.foreas.com

CONSTANT HEAD APPARATUS/ASTM D2434; AASHTO T215
TECHNICAL SPECİFATION MODEL S

Used to determine the permeability of granular-grained soils..Consists of: Permeameter stand
Constant-head permeability cell..Manometer tubes/valves
Constant-head tank

Nominal cell inside diam	75 mm
Cell wall	Transparent plastic
Take-off points	3
End plates	Anodized aluminum
Weight	1-2kg

Constant Level Tank: manufactured from transparent plastic with attachment for wall mounting...Manometers tubes comprising three glass tubes of constant bore, meter scale and connecting tubing for cell pressure take-off points, all mounted on a free-standing panel.



HAND-OPERATED HYDRAULIC SAMPLE EXTRUDER
TECHNICAL SPECİFATION MODEL S

Max load Cap	50kN
Ram travel	450-500mm
Weight	75-80kg



Adaptor with the size of 35, 38, 101.6, 106 and 152.4mm dia.



FORE TEST CİHAZLARI
İMALAT SAN. ve ULUSLARARASI TİC. A.Ş.
 "Yüksek Test Teknolojileri" www.foreas.com

RİFFLE BOXES


The sample splitter equipment is designed to halve/divide aggregates, soils, sands and gravel into two representative halves...Made of powder coated enameled steel



Item	Recommended Max Particle Size(mm) (BS)	Slot width(mm)	Number of Slots	Weight(kg)
	4,5	7	12	3-5
	12,5	19	10	
	25	38	8	
	42,4	64	8	

Rubber pastle and 2mx2m two quart. canvas

SOIL COLOR CHARTS



Nine constant hue charts displaying 322 colors..Apertures cut between adjacent colors for easy viewing of sample against color



FORE TEST CİHAZLARI
İMALAT SAN. ve ULUSLARARASI TİC. A.Ş.
"Yüksek Test Teknolojileri" www.foreas.com